



| Product | Weight (kg) |
|------------|-------------|
| PRO34L500 | 3,3 |
| PRO34L1000 | 5,6 |
| PRO34L2000 | 9,9 |
| PRO34L2500 | 12,0 |
| PRO34L3000 | 14,2 |
| PRO34L4000 | 18,6 |
| PRO34L5000 | 23,0 |

| | |
|------------------|-------------------------|
| Main tube | 50 x 2 mm |
| Braces | 16 x 2 mm |
| Alloy | EN-AW 6082 T6 (AlMgSi1) |

| | |
|------------------|-------------------------|
| Main tube | 50 x 2 mm |
| Braces | 20 x 2 mm |
| Alloy | EN-AW 6082 T6 (AlMgSi1) |

If you want to use this material, in order sign after code as /h. Static calculation on the request.

| Loading table | 2m | 4m | 6m | 8m | 10m | 12m |
|-----------------|--------|--------|-------|-------|-------|-------|
| Point load [kg] | 1800,0 | 1000,0 | 680,0 | 500,0 | 400,0 | 320,0 |
| Deflection [mm] | 4,6 | 13,5 | 27,6 | 47,9 | 74,8 | 105,3 |
| UDL [kg/m] | 930,0 | 455,0 | 202,0 | 112,0 | 76,0 | 49,0 |
| Deflection [mm] | 3,5 | 16,6 | 33,3 | 56,4 | 91,8 | 125,4 |

